



Submittal Data Sheet

1.5-Ton R32 Vista 2×2 Cassette Unit for VRV
FXZA18AAVJU

FEATURES

- 4-way, 3-way, and 2-way blow configurability
- Independently motorized louver outlets
- High efficiency DC fan motor with Auto fan speed control
- Low profile decoration panel design measures a mere 5/16" below the ceiling
- Integral condensate pump with up to 24-13/16" (630mm) lift from the drain outlet
- Independently configurable auxiliary heat on/off temperatures
- One decoration panel design color available

R-32 FEATURES

- Factory-installed integrated refrigerant leak sensor
- Dispersion Mode: Higher airflow rate for leak mitigation through circulation
- Terminal for connection, via optional relay PCB, to external alarms and monitoring systems



Image for reference purpose



Submittal Data Sheet
1.5-Ton R32 Vista 2×2 Cassette Unit for VRV
FXZA18AAVJU

PERFORMANCE

Indoor Unit Model No.	FXZA18AAVJU	Indoor Unit Name:	1.5-Ton R32 Vista 2×2 Cassette Unit for VRV
Type:	Cassette	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (BTU/hr):	18,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Rated Heating Capacity (BTU/hr):	20,000		

INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Airflow Rate (H/M/L) (CFM):	511/441/353
Power Supply Connections:	L1, L2, G	Sound Pressure (H/M/L) (dBA):	43/40/33
Min. Circuit Amps MCA (A):	0.6	Sound Power Level (dBA):	60
Max Overcurrent Protection (MOP) (A):	15		
Dimensions (HxWxD) (in):	10-1/4 x 22-5/8 x 22-5/8		
Net Weight (lb):	41.9		

Submittal Data Sheet

1.5-Ton R32 Vista 2x2 Cassette Unit for VRV
FXZA18AAVJU

DIMENSIONAL DRAWING

