



Submittal Data Sheet
2.0-Ton Ceiling Suspended Unit
FXHQ24MVJU

FEATURES

- One of our slimmest indoor units (less than 8â€³) fits any interior design
- Wide air discharge outlet distributes a comfortable airflow throughout the entire space
- Silent stream fan technology keeps sound pressure levels low
- Unit requires minimal installation space
- Standard Limited Warranty: 10-year warranty on compressor and all parts





Submittal Data Sheet
2.0-Ton Ceiling Suspended Unit
FXHQ24MVJU

PERFORMANCE

Indoor Unit Model No.	FXHQ24MVJU	Indoor Unit Name:	2.0-Ton Ceiling Suspended Unit
Type:	Ceiling Suspended	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	24,000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):	17,100	Rated Piping Length(ft):	
Cooling Input Power (kW):	0.130	Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	27,000		
Heating Input Power (kW):	0.13		

INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/L) (CFM):	710/600
Power Supply Connections:	L1, L2, Ground	Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	1	Gas Pipe Connection (inch):	5/8
Max Overcurrent Protection (MOP) (A):	15	Liquid Pipe Connection (inch):	3/8
Dimensions (HxWxD) (in):	7-11/16 x 55-1/8 x 26-3/4	Condensate Connection (inch):	1
Net Weight (lb):	80	Sound Pressure (H) (dBA):	44
Ext. Static Pressure (Rated/Max) (inWg):	/	Sound Power Level (dBA):	

Submittal Data Sheet **2.0-Ton Ceiling Suspended Unit** **FXHQ24MVJU**

DIMENSIONAL DRAWING

FXHQ24MVJU
Unit (in.)

