



Submittal Data Sheet

0.75 Ton R-32 Wall Mount Unit

FXAA09AAVJU

FEATURES

- Expanded lineup with the addition of the 5,400 Btuh size unit
- Up-down and left-right airflow direction control
- Efficient operation and year-round energy savings through Smart Variable Refrigerant Temperature (VRT) technology
- New D4 communication protocol which unlocks remote access to units through Daikin Hero
- Maintenance friendly design with removable drain pan

BENEFITS

- Factory-installed integrated refrigerant leak sensor
- Dispersion Mode: Higher airflow rate for leak mitigation through circulation
- Terminal for connection, via optional relay PCB, to external alarms and monitoring systems





Submittal Data Sheet

0.75 Ton R-32 Wall Mount Unit


FXAA09AAVJU

PERFORMANCE

Indoor Unit Model No.	FXAA09AAVJU	Indoor Unit Name:	0.75 Ton R-32 Wall Mount Unit
Type:	Wall Mounted	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	9,500	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Rated Heating Capacity (Btu/hr):	10,500		

INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/M/L) (CFM):	353/300/247
Power Supply Connections:	L1, L2, G		
Min. Circuit Amps MCA (A):	0.3	Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):	15	Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	11-5/8 x 33-13/16 x 9-3/4	Condensate Connection (inch):	5/8
		Sound Pressure (H/M/L) (dBA):	36/32/29
Net Weight (lb):	26.5	Sound Power Level (dBA):	54



Unit : in (mm)

