



Submittal Data Sheet

0.75-Ton Wall Mounted Daikin OTERRA Cooling Only System
FTK09BXVJURK09BXVJU

FEATURES

- Daikin Swing Compressor
- Indoor Quiet Operation
- Included Handheld Remote
- Titanium Apatite Air-Purifying Filter
- Anti-corrosion Treatment of Outdoor Heat Exchanger

INDOOR UNIT



BENEFITS

- Precharged Line set - 33 ft
- Cooling Operation Range - 50-115F
- 12 Year Parts and Compressor Registered Residential Warranty
- 5 year Parts and Compressor Commercial Warranty

OUTDOOR UNIT





Submittal Data Sheet

0.75-Ton Wall Mounted Daikin OTERRA Cooling Only System
FTK09BXVJURK09BXVJU

SYSTEM PERFORMANCE

Indoor Unit Model No.	FTK09BXVJU	Indoor Unit Name:	Daikin OTERRA 3/4 Ton AC only mini split indoor unit
Outdoor Unit Model No.	RK09BXVJU	Outdoor Unit Name:	0.75-Ton, Cooling only, Ductless ODU Daikin OTERRA
Rated Cooling Capacity (Btu/hr):	8,900	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Sensible Capacity (Btu/hr):		Rated Piping Length(ft):	25
Max/Min Cooling Capacity (Btu/hr):	10,200 / 4,400	Rated Height Difference (ft):	0.00
Cooling Input Power (kW):	2.610		
SEER2 (Non-Ducted/Ducted):	20.00 /		
EER2 (Non-Ducted/Ducted):	12.50 /		

SYSTEM DETAILS

Refrigerant Type:	R-410A	Cooling Operation Range (°F DB):	50 - 115
Holding Refrigerant Charge (lbs):	1.54		
Additional Charge (lb/ft):	0.21	Max. Pipe Length (Vertical) (ft):	49
Pre-charge Piping (Length) (ft):	33	Cooling Range w/Baffle (°F DB):	-4 - 115
Max. Pipe Length (Total) (ft):	66		
Max Height Separation (Ind to Ind ft):	0		



Submittal Data Sheet


0.75-Ton Wall Mounted Daikin OTERRA Cooling Only System
FTK09BXVJURK09BXVJU

INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Airflow Rate (HH/HM/L/SL) (CFM):	466/431/322/249/142
Power Supply Connections:	L1, L2, L3, Ground	Moisture Removal (Gal/hr):	0.1
Min. Circuit Amps MCA (A):		Gas Pipe Connection (inch):	3/8
Max Overcurrent Protection (MOP) (A):		Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	11-1/3 x 30-29/32 x 9-27/32	Condensate Connection (inch):	5/8
Net Weight (lb):	20.3	Sound Pressure (H/M/L/SL) (dBA):	44/37/30/19
Ext. Static Pressure (Rated/Max) (inWg):	/	Sound Power Level (dBA):	

DIMENSIONAL DRAWING - INDOOR UNIT

Model : FTK09/12B, FTX09/12B



Submittal Data Sheet


0.75-Ton Wall Mounted Daikin OTERRA Cooling Only System
FTK09BXVJURK09BXVJU

OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Compressor Stage:	Inverter
Power Supply Connections:	L1, L2, L3, Ground	Capacity Control Range (%):	-
Min. Circuit Amps MCA (A):	12.35	Airflow Rate (H) (CFM):	1083
Max Overcurrent Protection (MOP) (A):	15	Gas Pipe Connection (inch):	3/8
Max Starting Current MSC(A):		Liquid Pipe Connection (inch):	1/4
Rated Load Amps RLA(A):		Sound Pressure (H) (dBA):	46
Dimensions (HxWxD) (in):	21-11/16 x 26-1/2 x 11-3/16	Sound Power Level (dBA):	
Net Weight (lb):	53		

DIMENSIONAL DRAWING - OUTDOOR UNIT

Model : RK09/12B, RX09/12B





Submittal Data Sheet

0.75-Ton Wall Mounted Daikin OTERRA Cooling Only System

FTK09BXVJURK09BXVJU

INDOOR ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
AZAI6WSCDKB	DKN Residential Cloud Wi-Fi Adaptor for Single- and Multi-Zone System (S21)	No
AZAI6WSPDKC	DKN Plus Interface	No
BRC51D61	Wired Remote Controller Kit	No
DACA-CP1-1	Mini Aqua Condensate Pump	No
DACA-CP4-1	MINI WHITE PUMP KIT 100-250V	No
DTST-LTE-LA-A	Daikin One Lite (with Translation Adaptor for S21 only)	No
DTST-ONE-ADA-A	Daikin One+ Smart Thermostat for VRV, SkyAir, Single- and Multi-Zone System	No
KRP928BB2S	RA Interface Adaptor for DIII-Net -	No

OUTDOOR ACCESSORIES

PART NUMBER	DESCRIPTION	INCLUDED
BRC51D61	Wired Remote Controller Kit	No
KEH067A41E	Daikin BMS DrainPan Heater Small RX09,12 and RXN09,12	No
KKG067A41	Back protection wire net (09 & 12)	No
KPW937F4	Air direction adjustment grille (09 & 12)	No