



Submittal Data Sheet

0.6-Ton VISTA 2x2 Cassette Unit for VRV

FXZQ07TBVJU

FEATURES

- Six capacity options, including a new 5,800 Btu/h model
- 4-way, 3-way, and 2-way blow configurability
- Independently motorized louver outlets
- High efficiency DC fan motor with Auto fan speed control
- Low profile decoration panel design measures a mere 5/16" below the ceiling
- Integral condensate pump with up to 24-13/16" (630mm) lift from the drain outlet
- Independently configurable auxiliary heat on/off temperatures
- Direct outside air integration possible
- One decoration panel design color available: BYFQ60C3W2W (white)
- Universal Design award winning design
- Standard Limited Warranty: 10-year limited parts warranty

BENEFITS

- 24-7/16" x 24-7/16" decoration panel design simplifies ceiling coordination by eliminating overlap of adjacent ceiling tiles in a 2x2 ceiling grid
- Auto fan speed control can reduce operational energy input by intelligently adjusting the fan speed in response to room temperature
- Independently adjustable air flow louvers allow for a high degree of air distribution flexibility
- The optional space and presence sensor kit optimizes energy efficiency by automatically adjusting the set point temperature when no occupants are detected by the unit
- The optional space and presence sensor kit enhances occupant comfort by automatically adjusting the air flow louvers to avoid cold drafts and reduce stratification during heating operation



VRV





Submittal Data Sheet

0.6-Ton VISTA 2x2 Cassette Unit for VRV
FXZQ07TBVJU

PERFORMANCE

Indoor Unit Model No.	FXZQ07TBVJU	Indoor Unit Name:	0.6-Ton VISTA 2x2 Cassette Unit for VRV
Type:		Rated Cooling Conditions:	Indoor (°F DB/WB): / Ambient (°F DB/WB): /
Rated Cooling Capacity (Btu/hr):	7,500	Rated Heating Conditions:	Indoor (°F DB/WB): / Ambient (°F DB/WB): /
Sensible Capacity (Btu/hr):	5,500	Rated Piping Length(ft):	
Cooling Input Power (kW):	0.043	Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	8,500		
Heating Input Power (kW):	0.04		

INDOOR UNIT DETAILS


Power Supply (V/Hz/Ph):	208/230 / 60 / 1	Airflow Rate (H/M/L) (CFM):	307/264/229
Power Supply Connections:		Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	0.3	Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):	15	Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	10-1/4 x 22-5/8 x 22-5/8	Condensate Connection (inch):	1-1/32
Net Weight (lb):	35.3	Sound Pressure (H/M/L) (dBA):	32/30/26
Ext. Static Pressure (Rated/Max) (inWg):	N/A / N/A	Sound Power Level (dBA):	49

Submittal Data Sheet

0.6-Ton VISTA 2x2 Cassette Unit for VRV

FXZQ07TBVJU

DIMENSIONAL DRAWING



Note: For additional dimensional data and clearance information, refer to Engineering Data