



Submittal Data Sheet

2.0 Ton Wall Mount - R-32

FTXV24AVJU9

FEATURES

- 12 Year limited Warranty for Parts and Compressor
- Sound pressure as low as 19 dB(A)
- Washable Dry Filter
- Powerful Operation mode
- Auto fan speed control
- Quick warming function

BENEFITS

- Quiet operation
- Low ambient cooling operation down to -4°F (-20°C) with field setting and air adjustment grille
- Operating Range - Cooling (50°F - 114.8°F)
- Operating Range - Heating (-13°F - 64.4°F)
- 12 year limited parts and compressor warranty with online registration
- 5 year limited parts warranty for commercial applications
- Factory Installed Wi-Fi module - Simple App Set up





Submittal Data Sheet

2.0 Ton Wall Mount - R-32

FTXV24AVJU9

ELECTRICAL

Power Supply (V/Hz/Ph):
*See Engineering Manuals for other voltages.

*208-230 / 60 / 1

PIPING

Gas Connection:
(inch)

5/8

Liquid Connection:
(inch)

1/4

Drain Connection:
(inch)

5/8

SPECIFICATIONS

COOLING - Airflow Rate (cfm):		COOLING - Sound Level (dBA):		HEATING - Airflow Rate (cfm):		HEATING - Sound Level (dBA):	
High:	629	High:	52	High:	717	High:	49
Med:	501	Med:	45	Med:	572	Med:	43
Low:	378	Low:	39	Low:	466	Low:	38
SuperLow:	335	SuperLow:	34	SuperLow:	413	SuperLow:	34
Dimensions (HxWxD) (in):		11-5/8 x 39 x 10-3/8		Net Weight (lb):		27	





Submittal Data Sheet

2.0 Ton Wall Mount - R-32



FTXV24AVJU9

DIMENSIONAL DRAWING


FTXV24AVJU9




REQUIRED SPACE




WIRELESS REMOTE CONTROLLER (ARC480A83)



BLADE ANGLE



STANDARD LOCATIONS OF WALL HOLES



3D150967A